



Brand/Model	HTI HT-190	HTI HT-191	HTI HT-192	MASTECH MS6414	MASTECH MS6416	MASTECH MS6418	CEM LDM-60H	CEM LDM-80H	CEM LDM-100H	SNDWAY SW-S80	SNDWAY SW-S120
Measurement range	0.05-50m	0.05-70m	0.05-100m	0.05-40m	0.05-60m	0.05-80m	0.05-60m	0.05-80m	0.05-100m	0.05-80m	0.05-120m
Measuring Accuracy	±3.0mm	±3.0mm	±3.0mm	±1.5mm	±1.5mm	±1.5mm	±1.5mm	±1.5mm	±1.5mm	±2mm	±1.5mm
Measuring Unit	m/ft/in	m/ft/in	m/ft/in	m/ft/in	m/ft/in	m/ft/in	m/ft/in	m/ft/in	m/ft/in	m/ft/in	m/ft/in
Lase level/ Laser type	Class II /620-670 nm,<1mw	Class II /620-670 nm,<1mw	Class II /620-670 nm,<1mw	Class II /635nm, <1mW	Class II /635nm, <1mW	Class II /635nm, <1mW	Class II /635nm, <1mW	Class II /635nm, <1mW	Class II /635nm, <1mW	Class II /635nm, <1mW	Class II /635nm, <1mW
Calculate area And volume/ Pythagoras	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
Camera Measurement	NO	NO	NO	NO	NO	NO	NO	NO	NO	YES	YES
Max storage	20 Units	20 Units	20 Units	99 Units	99 ค่า	99 ค่า	20 ค่า	20 ค่า	20 ค่า	100 ค่า	100 ค่า
USB Connection	NO	NO	NO	NO	NO	NO	NO	NO	NO	YES	YES
Storage Temperature	0~40°C	0~40°C	0~40°C	0~40°C	0~40°C	0~40°C	-10~50°C	-10~50°C	-10~50°C	-20~60°C	-10~50°C
Auto cut off laser	60 s	60 s	60 s	20 s	20 s	20 s	50 s	50 s	50 s	20 s	20 s
Power supply	2/ 1.5V	2/ 1.5V	2/ 1.5V	3/ 1.5V	3/ 1.5V	3/ 1.5V	2/ 1.5V	2/ 1.5V	2/1.5V	3/1.2V	3/1.2V