



AS8900
Multi-Gas Monitor
O₂ / H₂S / CO / Combustible Gas

CNEX ExidICT3 Gc
国家认证 CNEx13.4165X



AS8901
Oxygen Monitor
Oxygen 0~30% VOL

CNEX ExidICT3 Gc
国家认证 CNEx13.4165X




AS8902
Combustible Gas Monitor
0~100% LEL

CNEX ExidICT3 Gc
国家认证 CNEx13.4165X



AS8903
Multi-Gas Monitor
Carbon Monoxide / Hydrogen Sulfide

CNEX ExidICT3 Gc
国家认证 CNEx13.4165X



AS8904
Carbon Dioxide Detector
PPM



AS8905
Sulfur Dioxide Detector
PPM

Gas Monitor / Detector

SPECIFICATIONS	AS8900	AS8901	AS8902	AS8903
Gas Type	Oxygen / Hydrogen Sulfide / Carbon Monoxide/Combustible Gas	Oxygen	Combustible Gas	Carbon Monoxide / Hydrogen Sulfide
Measuring Range	O ₂ : 0~30%VOL CO: 0~999 µmol/mol(ppm) H ₂ S: 0~500 µmol/mol(ppm) Combustible Gas: 0~100%LEL	0~30% VOL	0~100% LEL	CO: 0~999 ppm H ₂ S: 0~500 ppm
Resolution	0.1% / 1µmol/mol(ppm) / 1%	0.1%	1%	1 ppm
Measuring Principle	Electrochemical principle, life for 2 years			
Low / High Alarm	√			
Alarm Setting	√			
Alarm	Sound, Light Alarm. Adjustable Alarm values, Alarm sound up to 80 db.			
Operation Temperature	-10°C ~ 50°C			
Operation Humidity	15%-95%RH (Standard)			
Certificates	Explosion-proof protective enclosures designed according to following standard : JIG693-2004 ; JIG695-2003 ; JIG915-2008 ; & GB3836-2000			

GENERAL CHARACTERISTICS & PACKING INFORMATION	
Power	3.7V Li-battery
Product Net Weight	200g
Product Size	120.2 x 64.5 x 38.3mm
Packing	Gift box
Standard Quantity / Carton	24
Standard Carton Size	46x 45.5 x 55cm
Standard Carton Gross Weight	19.5kg

SPECIFICATIONS	AS8904	AS8905
Gas Type	Carbon Dioxide	Sulfur Dioxide
Measuring Range	350~9999 ppm	0~20 ppm
Resolution	1 ppm	1 ppm
Measuring Principle	Optics	Electrochemical principle, life for 2 years
Low /High Alarm	√	
Alarm Setting	√	
Alarm	Sound, Light Alarm. Adjustable Alarm values, Alarm sound up to 80 db.	
Operation Temperature	-10°C ~ 50°C	
Operation Humidity	15%-95%RH (Standard)	
Certificates	Explosion-proof protective enclosures designed according to following standard : JIG693-2004 ; JIG695-2003 ; JIG915-2008 ; & GB3836-2000	

GENERAL CHARACTERISTICS & PACKING INFORMATION	
Power	3.7V Li-battery
Product Net Weight	200g
Product Size	120.2 x 64.5 x 38.3mm
Packing	Gift box
Standard Quantity / Carton	24
Standard Carton Size	46x 45.5 x 55cm
Standard Carton Gross Weight	19.5kg

Gas Detector / External Sampling Pump



ติดต่อบริษัทฯ นีโอนิคส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@tools.in.th เว็บไซต์ www.tools.in.th

SPECIFICATIONS	AS8906	AS8907	AS8908	AS8909
Gas Type	Nitrogen Dioxide	Carbon Monoxide	Ozone	Hydrogen
Measuring Range	0~20 ppm	0~1000 ppm	0~1 ppm	0~1000 ppm
Resolution	1 ppm	1 ppm	0.01 ppm	1 ppm
Measuring Principle	Electrochemical principle, life for 2 years			
Low / High Alarm	√			
Alarm Setting	√			
Alarm	Sound, Light Alarm. Adjustable Alarm values, Alarm sound up to 80 db.			
Operation Temperature	-10°C ~ 50°C			
Operation Humidity	15%-95%RH (Standard)			
Certificates	Explosion-proof protective enclosures designed according to following standard : JIG693-2004 ; JIG695-2003 ; JIG915-2008 ; & GB3836-2000			

GENERAL CHARACTERISTICS & PACKING INFORMATION	
Power	3.7V Li-battery
Product Net Weight	200g
Product Size	120.2 x 64.5 x 38.3mm
Packing	Gift box
Standard Quantity / Carton	24
Standard Carton Size	46x 45.5 x 55cm
Standard Carton Gross Weight	19.5kg

SPECIFICATIONS	AS8930	SPECIFICATIONS	AS8700A
Velocity of Air-flow : 0.5SCFH (0.25LPM)		Gas Type	Carbon Monoxide
Gas samples can be collected away from 50 feet		Measuring Principle	Electrochemical Specific gas sensors, life for 3 years
For : AS8900 AS8901 AS8902 AS8903 AS8904 AS8905 AS8906 AS8907 AS8908 AS8909		Measuring Range	1~1000 (PPM)
		Resolution	1PPM
		Accuracy	±10 %
		Response Time	<60 sec
		Alarm	Alarm Buzzer
		Alarm Setting	√
		Battery Indication	√
		Auto Power Off	√
		Backlight Display	√
		Operation Temperature	0°C~50°C

GENERAL CHARACTERISTICS & PACKING INFORMATION		GENERAL CHARACTERISTICS & PACKING INFORMATION	
Product Net Weight	69g	Power	3*1.5V AAA batteries
Packing	Gift box	Product Net Weight	75g
Standard Quantity / Carton	40	Product Size	135 x 47 x 25mm
Standard Carton Size	51 x 34 x 46cm	Packing	Blister
Standard Carton Gross Weight	7.85kg	Standard Quantity / Carton	60
		Standard Carton Size	50 x 24 x 46cm
		Standard Carton Gross Weight	10.9kg

Nitrogen Dioxide Detector AS8906

Carbon Monoxide Detector AS8907

Ozone Detector AS8908

Hydrogen Detector AS8909

Carbon Monoxide Detector AS8700A
1~1000 (PPM)

External Sampling Pump AS8930
0.5SCFH (0.25LPM)