



Thermal Imaging Camera



Handheld Thermal Imaging Camera is widely used in the Medical, Archaeological, transport, Agriculture and so on.

Specification

Model	HT-02	HT-02D
Display	2.4" Color display	2.4" Color display
Resolution	60×60	32×32
Total pixels	3600	1024
FOV/Shortest focal length	20°×20°/0.5m	33°×33°
Thermal sensitivity	0.15°C	
Measuring mode	Infrared focal plane measuring temperature	
Temperature range	-20°C~300°C(-4°F~572°F)	
Measuring accuracy	±2% digital/±2°C	
Wavelength range	8~14μm	
Image frequency	6Hz	
Emissivity	0.1-1.0 Adjaseble	
Focus Mode	Fixed	
Palette	Iron colon,rainbow,black and white	
Image Storage	card(4G)	
File Format	bmp	
Set control	unit adjustment/Language/date time	
Power type	4*AA alkaline batteries	
Operating temperature	5°C~40°C	
Storage temperature	-20°C~50°C	
Humidity	10%RH to 80%RH	
Vibration	2G,IEC 60068-2-6	
Size	230×80×52mm	
Weight	320g	

HT-02/02D

LINE ID: @neonics



ติดต่อบริษัท นีโอนิคส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@tools.in.th เว็บไซต์ www.tools.in.th