

PRODUCT DATA SHEET



Salinity meter SB-1500PRO



Applications:

- ✔ Salt content of food and salt intake monitoring
- ✔ Standardization of taste in food manufacture
- ✔ Salt water swimming pool testing
- ✔ Hydroponic feed delivery testing

Features:

- ✔ Cup shape sensor
- ✔ Select the Manual measuring or Auto measuring
- ✔ Automatic temperature compensation (ATC)
- ✔ 5 Minutes after, off automatically

Technical Parameters:

- Measurement principle : Electrical conductivity method
- Measuring Range : 0.01% ~ 10.0%
- A.T.C (Automatic temperature compensation) : 0°C~98°C(0.01%~3.0%) / 20°C ~40°C(3.1%~10.0%)
- Resolution : 0.01% (0.01% ~ 2.99%) / 0.1%(3.0%~10.0%)
- Accuracy :
 - 0.01~2.00%(±0.1%) / 2.01~3.0%(±0.2%)
 - 3.1~4.0%(±0.3%) / 4.1~5.0%(±0.4%)
 - 5.1~8.0%(±0.5%) / 8.1~10.0%(±0.6%)
- Sodium measuring Range: 0~3999mg
- Resolution : 0.1mg(0~399.9mg) / 1mg(400~3999mg)
*Contained sodium in 100g of food.
- Temperature Range: 0.0°C~99.9°C
- Resolution : 0.1°C / Accuracy : ± 1°C
- Ambient temperature : 5°C~40°C / Max 95% R.H.non-condensing
- Auto Shut-off : After 5minutes, power-saving features
- Temperature compensation : A.T.C(Automatic)
- Display : LCD Screen
- Power source : 1.5V x 3PCS(Button cell batteries : LR44)
- Waterproof : Splash proof
- Dimensions : 21.4×3.4×3.4(cm) / 81g



ติดต่อบริษัท นีโอนิกส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@tools.in.th หรือ sale@neonics.co.th เว็บไซต์ www.tools.in.th

