

Film/Coating Thickness Gauge



GM200



GM210



GM211

Technical indicators	GM200	GM210	GM211
Measuring range	0~1.80mm/ 0~7.0mil	0~1800µm/ 0~70.9mil	0~1500µm/ 0~59mil/ 0~1.5mm
Error	±0.03mm	±(3%H±1µm)	≤150µm ±5µm; >150µm ±(3%H±1µm)
Resolution	0.01mm/1mil	0.1µm//1µm/ 0.1mil	0.1µm/1µm/ 0.1mil、0.001mm
Magnetic matrix minimum diameter	without	Φ12mm	Φ12mm
Magnetic substrate minimum thickness	without	0.5mm	0.5mm
Magnetic convex matrix minimum radius of curvature	without	2mm	2mm
Magnetic concave matrix minimum radius of curvature	without	11mm	11mm
Non-magnetic matrix minimum diameter	50mm	without	50mm
Non-magnetic matrix minimum thickness	0.5mm	without	0.5mm
Working temperature range	0~40°C		
Working humidity range	10~95%RH		
Peculiarity			
Zero / 2 o'clock and the basic check	√	√	√
Single/continuous/difference	√	√	√
Public English unit	√	√	√
LCD backlight shows	×	√	√
Auto power-off	√	√	√
Conventional			
Power supply	2*1.5 V AAA	2*1.5 V AAA batteries	
Product size	104.99*30.57*61.98mm	107.99*30.57*61.98mm	
Product weight	63.98g(No batteries)	64.79(No batteries)	

LINE ID: @neonics



ติดต่อบริษัท เนโอเนิกส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@tools.in.th เว็บไซต์ www.tools.in.th