

Portable Dissolved Oxygen Meter AMT07



AMT07

Features:

- Microprocessor based for fast and accurate measurements.
- Special viewing angle designed of waterproof housing IP57 rated. It floats on water.
- Large LCD display and Temperature Simultaneously.
- Simple to calibrate by one keyboard and automatic temperature compensation (ATC), Manual Salinity (MSC) and Altitude(MAC) Compensation.
- Multi-functions with Data-hold, Max/Min and shows PTS after calibration. Degree °C/°F are switchable.
- Low battery and consumption indicator. Auto power shut off after 10 minutes of non use.
- Easy to replace electrode module and the type of electrode would be recognized automatically and shown in display during insertion.

Specifications

	DO	O2	Temp
• Range	0~20.00mg/L	0~200%	0~90.0 °C
• Accuracy	±0.2	±2% FS	±0.2
• Resolution	0.01	0.1	0.1
• ATC	0~50 °C		
• MSC	0~50 ppt		
• MAC	0-20000 ft		
• Calibration	100% in air		
• Power	DC1.5V x 4 battery size:AAA/UM-4		
• Dimensions	Meter: 195 x 40 x 36 mm, Kits: 230 x 205 x 50 mm		
• Weight	Meter: 135g(with battery), Kits: 780g		

Portable Dissolved Oxygen Meter AMT08

Features:

- Microprocessor based for fast and accurate measurements.
- Waterproof housing IP57 rated. It floats on water.
- Large LCD display and Temperature Simultaneously.
- Auto Power Off

Specifications:

- Range: 0.0~19.9mg/L
- Resolution: 0.1mg/L
- Accuracy: ±0.5mg/L
- Temp.: 0.0~99.9 °C
- Temp. Resolution: 0.1 °C
- Temp. Accuracy: ±0.5 °C
- ATC: 5~45 °C
- Calibration Alarm: Yes
- Auto Off: After 10 minutes
- Power: 4 x 1.5V Button Cell
- Size: 170*37*37mm
- Weight: 90g



AMT08