



Vibration Meter

AR63A

10Hz~1KHz(Lo)
1KHz~15KHz(Hi)



Vibration Meter

AS63A

0.1~199.9m/s²



Vibration Meter

AR63B

10Hz~1KHz(Lo)
1KHz~15KHz(Hi)



Vibration Meter

AS63B

0.1~199.9m/s²



Vibration Meter

AR63C

10Hz~1KHz(Lo)
1KHz~15KHz(Hi)



Vibration Meter

AS63D

0.1~199.9m/s²

Vibration Meter

SPECIFICATIONS	AR63A	AR63B	AR63C
Vibration Pick-up	Piezoelectric Ceramic Accelerometer (Shear-type)		
Measuring Range of Acceleration	0.1~199.9m/s ² peak		
Measuring Range of Velocity	0.1~199.9mm/s rms		
Measuring Range of Displacement	0.001~1.999mm p-p		
Frequency Range of Acceleration	10Hz~1KHz(Lo)	1KHz~15KHz(Hi)	
Frequency Range of Velocity	10Hz~1KHz(Lo)		
Frequency Range of Displacement	10Hz~1KHz(Lo)		
Accuracy	±5% + 2digits		
Single Output	AC output 2V Peak (display full scale)		
Frequency Feature Selection	√	√	√
Measuring Mode Selection	√	√	√
Auto Power Off	√	√	√
Battery Indication	√	√	√
Backlight Display	√	√	√
Max Hold Function	---	√	---
Temp. Measuring	---	√	---
°C / °F Selection	---	√	---

GENERAL CHARACTERISTICS & PACKING INFORMATION

	AR63A	AR63B	AR63C
Power	9V battery	9V battery	2*1.5V AAA batteries
Product Net Weight	147g	137g	76g
Product Size	183 x 67 x 30mm	150 x 70 x 30mm	150 x 35 x 25mm
Packing	Aluminum Box	Aluminum Box	Gift box
Standard Quantity / Carton	12	12	40
Standard Carton Size	52 x 43 x 32.5cm	52 x 43 x 32.5cm	52 x 40 x 49cm
Standard Carton Gross Weight	11.93kg	14.14kg	12.65kg

Vibration Meter

SPECIFICATIONS	AS63A	AS63B	AS63D
Vibration Pick-up	Piezoelectric Ceramic Accelerometer (Shear-type)		
Measuring Range of Acceleration	0.1~199.9m/s ² peak		
Measuring Range of Velocity	0.1~199.9mm/s rms		
Measuring Range of Displacement	0.001~1.999mm p-p		
Frequency Range of Acceleration	10Hz~1KHz(Lo)	1KHz~15KHz(Hi)	
Frequency Range of Velocity	10Hz~1KHz(Lo)		
Frequency Range of Displacement	10Hz~1KHz(Lo)		
Accuracy	±5% + 2digits		±10% + 2digits
Single Output	AC output 2V Peak (display full scale)		
Frequency Feature Selection	√	√	√
Measuring Mode Selection	√	√	√
Auto Power Off	√	√	√
Battery Indication	√	√	√
Backlight Display	√	√	√
Max Hold Function	---	√	---
Temp. Measuring	---	√	---
°C / °F Selection	---	√	---

GENERAL CHARACTERISTICS & PACKING INFORMATION

	AS63A	AS63B	AS63D
Power	9V battery	9V battery	2*1.5V AA batteries
Product Net Weight	147g	155g	115g
Product Size	183 x 67 x 30mm	159 x 66 x 31mm	180 x 42.5 x 30mm
Packing	Gift box	Gift box	Gift box
Standard Quantity / Carton	10	12	20
Standard Carton Size	45 x 32 x 55cm	45 x 32 x 55cm	45 x 32 x 55cm
Standard Carton Gross Weight	14.17kg	16.33kg	13.08kg