

LASER DISTANCE METER

MS6414 / MS6416 / MS6418 / MS64100



MS6414

DISTANCE
0.05m~40m



MS6416

DISTANCE
0.05m~60m



MS6418

DISTANCE
0.05m~80m



MS64100

DISTANCE
0.05m~100m



Specifications	MS6414	MS6416	MS6418	MS64100
Specifications	Range			
Distance	0.05~40m/2~131"	0.05~60m/2~197"	0.05~80m/2~263"	0.05~100m/2~329"
Accuracy	±1.5mm/± 0.06"	±1.5mm/± 0.06"	±1.5mm/± 0.06"	±1.5mm/± 0.06"
Unit	meter/inch/feet	meter/inch/feet	meter/inch/feet	meter/inch/feet
Length	9999m	9999m	9999m	9999m
Area	99999m ²	99999m ²	99999m ²	99999m ²
Volume	99999m ³	99999m ³	99999m ³	99999m ³
Features				
Laser	Assisted laser ray measurements			
APO	Auto Power Off			
Data Logging	99 groups			
Area & Volume	Area & Volume Calculation			
Foot level	Auxiliary foot level measurement			
Backlight	Display Backlight			
General				
Power Supply	3x1.5V AAA Batteries			
Product Size	120x60x28mm/4.2"x2.2"x0.9"			
Product Weight	175g/0.4lb			
Safety Rating	CE(EMC) RoHS			



ติดต่อบริษัท นีโอนด์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@tools.in.th เว็บไซต์ www.tools.in.th