

## DIGITAL MULTIMETER MS8261 / MS8264 / MS8269



### MS8261

**VOLTAGE** DC 1000V  
AC 750V


**CURRENT** DC 10A  
AC 10A



### MS8264

**VOLTAGE** DC 1000V  
AC 750V

**CURRENT** DC 10A  
AC 10A



### MS8269

**VOLTAGE** DC 1000V  
AC 750V

**CURRENT** DC 10A  
AC 10A



### Specifications

Specifications	Range	MS8261	MS8264	MS8269
DC Voltage	200mV/2V/20V/200V	±(0.5%+1)	±(0.5%+1)	±(0.5%+1)
	1000V	±(0.8%+2)	±(0.8%+2)	±(0.8%+2)
AC Voltage	2V/20V/200V	±(0.8%+3)	±(0.8%+3)	±(0.8%+3)
	750V	±(1.2%+3)	±(1.2%+3)	±(1.2%+3)
DC Current	2mA	±(0.8%+1)		
	20mA/200mA	±(1.5%+1)	±(1.5%+1)	
	200mA			±(1.5%+1)
AC Current	2mA	±(2.0%+5)	±(2.0%+5)	±(2.0%+5)
	200mA	±(1.0%+3)	±(1.0%+3)	
	10A	±(1.8%+3)	±(1.8%+3)	±(1.8%+3)
Resistance	200Ω	±(0.8%+3)	±(0.8%+3)	±(0.8%+3)
	2KΩ/20KΩ/200KΩ/2MΩ	±(0.8%+1)		±(0.8%+1)
	20MΩ	±(1.0%+2)		±(1.0%+2)
	2KΩ/20KΩ/200KΩ/2MΩ/20MΩ		±(0.8%+1)	
Capacitance	200MΩ	±(5.0%+10)	±(5.0%+10)	
	2nF/20nF/200nF/2μF/20μF	±(4%+3)	±(4%+3)	
	20nF/200nF/2μF			±(4%+8)
	200μF			±(4%+15)
Frequency	200kHz		±(1.5%+5)	
Inductance	20mH/200mH/2H/20H			±(3%+8)
Temperature	-20°C~0°C		±(5.0%+4)	±(5.0%+4)
	1°C~400°C		±(1.0%+3)	±(1.0%+3)
	401°C~1000°C		±2%	±2%

### Features

Features	MS8261	MS8264	MS8269
Display	counts	2000	2000
APO	Auto Power Off	●	●
Transistor hFE	0~1000	●	●
Diode	2.8V	●	●
Continuity Buzzer		<30Ω	<60Ω
Data Hold		●	●
Display Backlight		●	●
LBD	Low Battery Display	●	●

### General

Power Supply	1x9V 6F22 Battery
Product Size	195mm×92mm×55mm/7.7"×3.6"×2.2"
Product Weight	380g/0.83lb
Safety Rating	CAT II 1000V / CAT III 600V RoHS

ติดต่อบริษัท นีโวนิคส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@tools.in.th เว็บไซต์ www.tools.in.th