

ติดต่อบริษัท นีโอนิคส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@tools.in.th เว็บไซต์ www.tools.in.th

DIGITAL MULTIMETER MS8265 / MS8268



MS8265

VOLTAGE DC 1000V
AC 750V

CURRENT DC 10A
AC 10A



MS8268

VOLTAGE DC 1000V
AC 750V

CURRENT DC 10A
AC 10A



Specifications		MS8265	MS8268
Specifications	Range	Accuracy	
DC Voltage	200mV	±(0.05%+5)	
	2V/20V/200V	±(0.1%+5)	
	1000V	±(0.15%+5)	
	400mV/4V/40V/400V	±(0.7%+2)	
	1000V	±(0.8%+2)	
AC Voltage	2V(50~60Hz)	±(0.5%+15)	
	20V/200V(50~60Hz)	±(0.8%+15)	
	750V(50~60Hz)	±(1.0%+15)	
	2V(40~400Hz)	±(1.0%+15)	
	20V/200V(40~400Hz)	±(1.0%+50)	
	750V(40~400Hz)	±(1.2%+50)	
	400mV	±(3%+3)	
	4V/40V/400V	±(0.8%+3)	
750V	±(1.0%+3)		
DC Current	2mA/200mA	±(0.5%+10)	
	400µA/4000µA/40mA/400mA	±(1.2%+3)	
	10A	±(2.0%+20)	±(2.0%+5)
AC Current	2mA	±(0.8%+20)	
	200mA	±(1.2%+20)	
	400µA/4000µA/40mA/400mA	±(1.5%+5)	
10A	±(2.5%+50)	±(3.0%+7)	
Resistance	200Ω	±(0.5%+10)	
	2KΩ/20KΩ/200KΩ/2MΩ/20MΩ	±(0.5%+5)	
	200MΩ	±(5%+20)	
	400Ω/4kΩ/40KΩ/400KΩ/4MΩ	±(1.2%+2)	
	40MΩ	±(2.0%+5)	
Capacitance	20nF/200nF/2µF/20µF/200µF	±(4%+20)	
	4nF	±(5.0%+5)	
	40nF/400nF/4µF/40µF/200µF	±(3.0%+3)	
Frequency	20KHz	±(1.5%+15)	
	9.999Hz~199.9kHz	±(2.0%+5)	
Duty Cycle	5%~95%	±(2.0%+2)	
Features			
Display	counts	20000	4000
Auto Ranging	Auto & Manual		●
APO	Auto Power Off	●	●
Sound & Light Warning	For incorrectly inserting the input plugs	●	●
REL	Relative Measurement		●
Transistor hFE	0~1000	●	●
Diode	2.8V	●	●
Continuity Buzzer	≤50Ω	●	●
Data Hold		●	●
Display Backlight		●	●
LBD	Low Battery Display	●	●
General			
Power Supply		1x9V6F22	3x1.5V AAA
Product Size	195x92x55mm/7.7x3.6x2.2"		
Product Weight	400g/0.9lb		
Safety Rating	CAT II 1000V / CAT III 600V RoHS		

● Feature Difference