

# PRODUCT DATA SHEET

## MD917 Moisture meter for concrete



Concrete Wall Moisture Meter MD917 Range 0~40% is a precision instrument adopting HF electromagnetic waves to measure the moisture content ratio without damaging the object under test.

Precision instrument adopting HF electromagnetic waves to measure the moisture content ratio without damaging the object under test.

- Measurement through HF electromagnetic sensing
- 10 different at option
- Automatic temperature compensation
- Setting of upper limit of moisture content ratio, prompting of overrunning
- Ultra-large LCD ensuring clear readings
- Automatic prompting of low voltage

### Feature:

- Range of measurement: 0 to 40%
- Accuracy: (1% 1)
- Resolution: 0.5%
- Environment:
  - temperature: - 5 ~ 40
  - Humidity: 0 ~ 80% Rh
- Power supply: 3 × 1.5V AAA battery
- Weight: 95 g(Not including battery)
- Size: 132 × 67 ×26mm



Cement floor inspection



Marble Inspection



Flooring Inspection



Gypsum Board Inspection



Tile Inspection



Wall Inspection

ติดต่อบริษัท นีโอนิกส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@tools.in.th หรือ sale@neonics.co.th