



Tube Rollers

Drawell tube rollers provide a gentle and highly efficient rolling motions, ideal for mixing blood samples, viscous substances and liquid-solid suspensions. Used in a variety of applications, such as the prevention of blood coagulation and immune precipitation, etc.

MX-T6-Pro

LCD Digital Tube Roller

Features:

- LCD displays the speed and time
- Speed range of 10~70rpm
- Six roller design for gentle rolling and easy to clean
- Continuous or timer operation

MX-T6-S

Tube Roller

Features:

- Speed range of 0~70rpm
- Six roller design for gentle rolling and easy to clean



LCD display



Timer



Specifications

	MX-T6-Pro	MX-T6-S
Amplitude	24mm	24mm
Motor type	DC motor	DC motor
Rocking motion	Rocking and rolling	Rocking and rolling
Amplitude	24mm	24mm
Max. load capacity	4kg	4kg
Number of rollers	6	6
Roller size [length]	280mm	280mm
Speed range	10 ~70rpm	0~70rpm
Speed display	LCD	Scale
Timer	Yes	-
Timer display	LCD	-
Time setting range	1~1199min	-
Operation mode	Continuous / timed	Continuous
Voltage	100~240V,50/60Hz	100~240V,50/60Hz
Power	30W	25W
Dimension [D×W×H]	450×260×120mm	450×260×120mm
Weight	5.1kg	4.5kg
Permissible ambient temperature and humidity	5~40°C,80%	5~40°C,80%
Protection class	IP21	IP21

Line ID: @neonics



ติดต่อบริษัท เนโอเนิกส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@tools.in.th เว็บไซต์ www.neonics.biz