



Monitors

	QC-1	SM-1	DM-1	DM-2
	Quick Check Monitor 	Single TDS Monitor 	Dual TDS Monitor 	Dual TDS Monitor 
	<ul style="list-style-type: none"> • With the push of a button, the unit displays a green or red light, indicating good water quality or that service is required, respectively • Tests for TDS or conductivity levels • Eight programmable set points (by dip switch) • Bright LED lights • Installs quickly and easily. Simple to use • Comes equipped with 1/4" T-fitting (also available with 3/8" or 1/2") 	<ul style="list-style-type: none"> • Displays the TDS level of a single water line • Works with the push of a button • Auto-off function conserves battery power; unit shuts off automatically after 10 minutes of non-use • Comes equipped with 1/4" T-fitting (also available with 3/8" or 1/2") 	<ul style="list-style-type: none"> • Displays TDS levels of the feed water and product water with in & out sensors • A crucial device for any water filter system • Great instant check for system performance • Comes equipped with 1/4" T-fittings (also available with 3/8" or 1/2") • Installs in minutes 	<p>All the benefits of the DM-1, plus:</p> <ul style="list-style-type: none"> • A large, easy-to-read LCD display • Splashproof housing • Shielded, water-resistant cables • Sliding bracket with variable mounting options • Sleek design • Longer sensor cables
RANGE	0-5000 ppm (0-9999 μ S)	0-9990 ppm	0-9990 ppm	0-9990 ppm
ACCURACY	+/- 3%	+/- 2%	+/- 2%	+/- 2%
RESOLUTION	n/a	1 ppm	1 ppm	1 ppm
ATC	n/a	Yes (1 - 65°C)	Yes (1 - 65°C)	Yes (1 - 65°C)
CALIBRATION	Factory calibrated only	Analog to any point	Analog to any point	Analog to any point
SET POINT	Eight options (max 50 ppm / 100 μ S)	n/a	n/a	n/a
ALARM	Red/green light (no audible alarm)	n/a	n/a	n/a
SENSOR	1/4" with T-fitting	1/4" with T-fitting	2 x 1/4" with T-fittings	2 x 1/4" with T-fittings
SENSOR CABLE LENGTH	62.2 cm (24.5") shielded cable	62.2 cm (24.5") shielded cable	62.2 cm (24.5")	116.8 cm (46") shielded cable
POWER SOURCE	4 x 1.5V button cell (included)	2 x 1.5V button cell batteries (incl.)	2 x 1.5V button cell batteries (incl.)	2 x AA batteries
BATTERY LIFE	Approx. 1 year	Approx. 1,000 hours of usage	Approx. 1,000 hours of usage	Approx. 750 hours of usage
DIMENSIONS	7.6 x 2 x 4.7 cm (3 x .8 x 1.9 in)	7.6 x 2 x 4.7 cm (3 x .8 x 1.9 in)	7.6 x 2 x 4.7 cm (3 x .8 x 1.9 in)	11.6 x 6.8 x 1.8 cm (4.6 x 2.6 x .7 in)
WEIGHT	39.7 g (1.4 oz)	79.4 g (2.8 oz)	79.4 g (2.8 oz)	201.3 g (7.1 oz)

ติดต่อบริษัท นีโอนิคส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@tools.in.th เว็บไซต์ www.tools.in.th

