

SM2234plus Non-contact Tachometer



Feature:

- Large LCD display for easy viewing (5 digits of 18 mm).
- Sampling time: 0.8 seconds (at more than 1000 RPM).
- Automatic range selection.
- Memory pair to the maximum, minimum and last values.
- Measuring speed: 2.5 to 99,999 RPM.

Specifications:

- PM2.5 Measuring Range: 0 ~ 500 μ g/m³
- Single/ Composite Response Time: <1s, \leq 10s
- Resolution: 1 μ g/m³
- Counting Efficiency of Particulate Matter : 50%@ 0.3 μ m; 98%@ \geq 0.5 μ m
- Mass Concentration Consistency of Particulate: \pm 10% @ 100 ~ 500 μ g/m³; \pm 10 μ g/m³; @ 0 ~ 100 μ g
- Temperature Measuring Range: -10.0~50.0 $^{\circ}$ C
- Temperature Accuracy: \pm 1.0 $^{\circ}$ C
- Humidity Measuring Range: 0%~99%RH
- Humidity Accuracy: \pm 10%RH
- PM2.5 Sensor: PLANTOWER Laser Particulate Matter Sensor
- Working time after full charging: > 4.5 hours
- Auto Power off: 30 minutes (will not auto shut down while charging)
- Charging/ Battery: DC 5V, 500mA, USB Connector / Li-ion 580mAh
- Working Temperature: -10.0 $^{\circ}$ C~ 50.0 $^{\circ}$ C, 0%~99%RH

ติดต่อ บริษัท นีโอนิคส์ จำกัด

333/81 ถนนเลียบวารี แขวงโคกแฝด เขตหนองจอก กรุงเทพฯ 10530

Tel: 061-8268939, 098-4795684 E-mail: sale@tools.in.th และ sale@neonics.co.th

www.neonics.co.th